

(19) United States

(12) Patent Application Publication (10) Pub. No.: US 2017/0217296 A1 NOMURA et al.

(43) Pub. Date:

Aug. 3, 2017

(54) FRAMEWORK STRUCTURE OF **BODY-ON-FRAME VEHICLE**

(71) Applicants: TOYOTA JIDOSHA KABUSHIKI KAISHA, Toyota-shi (JP); TOYOTA SHATAI KABUSHIKI KAISHA,

Kariya-shi (JP)

(72) Inventors: Kenta NOMURA, Nagoya-shi (JP); Hideo KAJINO, Niwa-gun (JP)

Assignees: TOYOTA JIDOSHA KABUSHIKI KAISHA, Toyota-shi (JP); TOYOTA SHATAI KABUSHIKI KAISHA,

Kariya-shi (JP)

(21) Appl. No.: 15/379,822

(22)Filed: Dec. 15, 2016

(30)Foreign Application Priority Data

Feb. 2, 2016 (JP) 2016-017964

Publication Classification

(51) Int. Cl. B60K 1/04 (2006.01)B62D 25/20 (2006.01)B60R 19/02 (2006.01)B60K 6/28 (2006.01) B62D 23/00 (2006.01)(2006.01)B62D 21/15

(52) U.S. Cl.

CPC B60K 1/04 (2013.01); B62D 23/005 (2013.01); B62D 21/157 (2013.01); B60R 19/02 (2013.01); B62D 21/152 (2013.01); B60K 6/28 (2013.01); B62D 25/2009 (2013.01); B60Y 2200/92 (2013.01); B60Y 2306/01 (2013.01); B60Y 2200/91 (2013.01); B60Y 2410/124 (2013.01); B60K 2001/0433 (2013.01); Y10S 903/907 (2013.01)

(57)**ABSTRACT**

A framework structure of a body-on-frame vehicle, the framework structure comprises a first framework, a second framework, and a battery. The first framework includes: a pair of left and right side rails extending in a vehicle body front-and-rear direction, a first cross-member and a second cross-member, both extending in a vehicle body left-andright direction and linking the side rails. The second framework is structured in a rectangular shape in plan view and includes: a front cross portion and a rear cross portion that are formed in chamber shapes and extend in the vehicle body left-and-right direction, and a left side cross portion and a right side cross portion that are formed in chamber shapes and extend in the vehicle body front-and-rear direction. The battery is disposed in a cavity surrounded by the first framework and the second framework.

